

60001740**COATED-R400-YELLOW GLASSINE 1740**

Face	One side coated paper is designed for high-end, pressure sensitive label applications. This grade features excellent opacity and high brightness combined with a semi-gloss finish for good flexographic, offset or rotogravure printing.
Adhesive	Acrylic based, removable adhesive for general use with long term removability.
Liner	Yellow, supercalandered siliconised glassine paper. Specially designed for high speed conversion, punching and perforation. Transparency allows its use in automatic dispensing system.

	Method	Unit	Target	
Face				
Basis Weight	ISO 536	g/m ²	80±2	
Thickness	ISO 534	µm	69±4	
Whiteness CIE D65/10 Top	ISO 11475	%	120±4	
Opacity	ISO 2471	%	88±3	
Brightness D65/10 Top		%	97±3	
Adhesive				
Peel adhesion 90°	FTM 2 st.st	N/m	min. 40	(min. 1 N/25mm)
Loop Tack	FTM 9 glass	N/m	min. 120	(min. 3 N/25mm)
Min. appl temperature		°C	0	
Service temperature		°C	-20 / +80	
Liner				
Basis Weight	ISO 537	g/m ²	61±2	
Thickness	ISO 534	µm	53±2	
Tensile strength MD	ISO 1924	kN/m	6.3	
Transparecy		%	50	
Laminate				
Thickness	ISO 534	µm	128±5	

Application and use

The product is suitable for removable labels for stores and supermarkets, process labelling applications and industrial labelling.

Converting and Printing

Surface is suitable for excellent print quality by all conventional print technologies and thermal transfer printing.

Packaging

The rolls are sliced according to customer requirements, packed with shrink films and paperboards are placed on sides. They are delivered on pallets. Product description labels are fixed on rolls.

Shelf Life and Storage Conditions

Two years when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 22 °C ± 2 °C with a relative humidity of 50 %, ± 5%.

All information and recommendations about FRIMPEKS products are based on our existing knowledge and experiences but do not mean a guarantee or warranty. As the products are used for different applications we recommend to check suitability of product prior to use. All information is subject to change without notice.