

60001205**COPYLASER-P120-WHITE KRAFT 70 1205**

Face White, woodfree uncoated machine finished paper with good opacity. This paper is suitable for multifunctional information labelling, especially designed for ink jet, lasers and photocopiers.

Adhesive Acrylic based, permanent adhesive for A4 applications. Specially designed for roll to sheet conversion e.g. for copier and laser printer products with good heat resistance and adhesion on different substrates. Adhesive has very good cuttability with reduced edge bleed.

Liner White, woodfree kraft backing paper for optimal layflat performance.

	Method	Unit	Target	
Face				
Basis Weight	ISO 536	g/m ²	70±1	
Thickness	ISO 534	µm	90±3	
Whiteness	CIE		164	
Opacity	ISO	%	92	
Adhesive				
Peel adhesion 90°	FTM 2 st.st	N/m	min.200 or PT	(min. 5 N/25mm or Paper Tear)
Loop Tack	FTM 9 glass	N/m	min.350	(min. 8,75 N/25mm)
Min. appl temperature		°C	0	
Service temperature		°C	-20 / +80	
Liner				
Basis Weight	ISO 537	g/m ²	70±2	
Thickness	ISO 534	µm	69±2	
Tensile strength MD	ISO 1924	kN/m	5.6	
Laminate				
Thickness	ISO 534	µm	162±5	

Application and use

For use in multifunctional information labelling, VIP labelling.

Converting and Printing

This product is designed for the manufacture of A4 sheets for use in laserprinters, copiers, inkjet printers. It is ideal for office use and information labelling such as address, instruction. The product has tight release property to avoid predispending during printing or copying process.

Packaging

The rolls are sliced according to customer requirements, packed with shrink films and paperboards are placed on sides. They are delivered on pallets. Product description labels are fixed on rolls.

Shelf Life and Storage Conditions

Two years when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 22 °C ± 2 °C with a relative humidity of 50 %, ± 5%.

All information and recommendations about FRIMPEKS products are based on our existing knowledge and experiences but do not mean a guarantee or warranty. As the products are used for different applications we recommend to check suitability of product prior to use. All information is subject to change without notice.