

60002300
ECO THERMAL-P100-YELLOW GLASSINE 2300

| | |
|-----------------|---|
| Face | A white non-topcoated paper that is coated with black imaging thermosensitive coating. This paper has limited resistance to thermal image scratching or smudging with normal stability against environmental influences such as heat, humidity, light, lanolin, ethanol, plasticizer and water. The image may fade over a period of time if exposed to high humidity and light. |
| Adhesive | Acrylic based, permanent adhesive for general use. Suitable for numerous applications on clean, dry and flat surfaces, including slightly rough and curved substrates. It's not suitable for wet applications. Excellent performance during slitting, high speed matrix-stripping and automatic labelling. |
| Liner | Yellow, supercalandered siliconised glassine paper. Specially designed for high speed conversion, punching and perforation. Transparency allows its use in automatic dispensing system. |

| | Method | Unit | Target | |
|-----------------------|-------------|------------------|---------------|---------------------------------|
| Face | | | | |
| Basis Weight | ISO 536 | g/m ² | 78±5 | |
| Thickness | ISO 534 | µm | 85±5 | |
| Smoothness (Bekk) | | S | min. 220 | |
| Opacity | ISO 2471 | % | min.90 | |
| Adhesive | | | | |
| Peel adhesion 90° | FTM 2 st.st | N/m | min.300 or PT | (min. 7,5 N/25mm or Paper Tear) |
| Loop Tack | FTM 9 glass | N/m | min.440 | (min. 11 N/25mm) |
| Min. appl temperature | | °C | 0 | |
| Service temperature | | °C | -20 / +50 | |
| Liner | | | | |
| Basis Weight | ISO 537 | g/m ² | 61±2 | |
| Thickness | ISO 534 | µm | 53±2 | |
| Tensile strength MD | ISO 1924 | kN/m | 6.3 | |
| Transparecy | | % | 50 | |
| Laminate | | | | |
| Thickness | ISO 534 | µm | 145±5 | |

Application and use

This product is designed for use in thermal printing system at printing speeds up to 8 inch /200 mm per sec (based on printer's set up). Typical applications are information labelling such as price and weigh marking (e.g. fruit, vegetable, deli labels) and other short life retail and logistics (addres, warehouse) end-uses.

Converting and Printing

Suitable for water based flexo printing. We recommend to check suitability for other printing methods.

Packaging

The rolls are sliced according to customer requirements, packed with shrink films and paperboards are placed on sides. They are delivered on pallets. Product description labels are fixed on rolls.

All information and recommendations about FRİMPEKS products are based on our existing knowledge and experiences but do not mean a guarantee or warranty. As the products are used for different applications we recommend to check suitability of product prior to use. All information is subject to change without notice.

FRİMPEKS KİMYA VE ETİKET SAN TİC. A.Ş.

Mermerciler Sanayi Sitesi 8. Cad. No:15 34520, Beylikdüzü, İstanbul / TÜRKİYE

T : + 90 (212) 876 07 10

F : + 90 (212) 876 07 17

e-mail : info@frimpeks.com.tr

www.frimpeks.com.tr



SELF ADHESIVE LABELSTOCKS**Shelf Life and Storage Conditions**

One year when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 22 °C ± 2 °C with a relative humidity of 50 %, ± 5%. Face paper has a slight tendency to discolour after one year, but this doesn't effect the scannability of the barcodes.

All information and recommendations about FRİMPEKS products are based on our existing knowledge and experiences but do not mean a guarantee or warranty. As the products are used for different applications we recommend to check suitability of product prior to use. All information is subject to change without notice.

FRİMPEKS KİMYA VE ETİKET SAN TİC. A.Ş.

Mermerciler Sanayi Sitesi 8. Cad. No:15 34520, Beylikdüzü, İstanbul / TÜRKİYE

T : + 90 (212) 876 07 10

F : + 90 (212) 876 07 17

e-mail : info@frimpeks.com.tr

www.frimpeks.com.tr

