

60002710**PP CLEAR 50 TC-P200-WHITE GLASSINE 2710**

Face	A bi-axially oriented, gloss clear, topcoated polypropylene film.
Adhesive	Acrylic based, permanent adhesive for general use. Suitable for numerous applications on clean, dry and flat surfaces, including slightly rough and curved substrates. It's not suitable for wet applications. Excellent performance during slitting, high speed matrix-stripping and automatic labelling.
Liner	White, supercalandered siliconised glassine paper. Specially designed for high speed conversion, punching and perforation. Transparency allows its use in automatic dispensing system.

	Method	Unit	Target	
Face				
Basis Weight	ISO 536	g/m ²	47±1	
Thickness	ISO 534	µm	51±1	
Adhesive				
Peel adhesion 90°	FTM 2 st.st	N/m	min. 280	(min. 7 N/25mm)
Loop Tack	FTM 9 glass	N/m	min. 320	(min. 8 N/25mm)
Min. appl temperature		°C	0	
Service temperature		°C	-20 / +80	
Liner				
Basis Weight	ISO 537	g/m ²	61±2	
Thickness	ISO 534	µm	53±2	
Tensile strength MD	ISO 1924	kN/m	6.3	
Transparency		%	50	
Laminate				
Thickness	ISO 534	µm	115±5	

Application and use

For use in labelling of quality products such as luxury items, cosmetics, toiletries and household chemicals requiring durability and resistance to chemicals or moisture.

Converting and Printing

Topcoated surface is suitable for printing by the usual printing technologies including letterpress, flexo, gravure and screen printing.

Packaging

The rolls are sliced according to customer requirements, packed with shrink films and paperboards are placed on sides. They are delivered on pallets. Product description labels are fixed on rolls.

Shelf Life and Storage Conditions

Two years when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 22 °C ± 2 °C with a relative humidity of 50 %, ± 5%.

All information and recommendations about FRIMPEKS products are based on our existing knowledge and experiences but do not mean a guarantee or warranty. As the products are used for different applications we recommend to check suitability of product prior to use. All information is subject to change without notice.