

**60001360**
**VELLUM EXTRA-P100-YELLOW GLASSINE 1360**

<b>Face</b>	An uncoated, surface-sized woodfree supercalendered paper with smooth surface. Specially designed for logistics labelling.
<b>Adhesive</b>	Acrylic based, permanent adhesive for general use. Suitable for numerous applications on clean, dry and flat surfaces, including slightly rough and curved substrates. It's not suitable for wet applications. Excellent performance during slitting, high speed matrix-stripping and automatic labelling.
<b>Liner</b>	Yellow, supercalendered siliconised glassine paper. Specially designed for high speed conversion, punching and perforation. Transparency allows its use in automatic dispensing system.

	Method	Unit	Target	
<b>Face</b>				
Basis Weight	ISO 536	g/m <sup>2</sup>	70±1	
Thickness	ISO 534	µm	67±3	
Whiteness CIE		%	147	
Roughness Bendtsen		ml/min	35	
<b>Adhesive</b>				
Peel adhesion 90°	FTM 2 st.st	N/m	min.300 or PT	(min. 7,5 N/25mm or Paper Tear)
Loop Tack	FTM 9 glass	N/m	min.440	(min. 11 N/25mm)
Min. appl temperature		°C	0	
Service temperature		°C	-20 / +80	
<b>Liner</b>				
Basis Weight	ISO 537	g/m <sup>2</sup>	61±2	
Thickness	ISO 534	µm	53±2	
Tensile strength MD	ISO 1924	kN/m	6.3	
Transparecy		%	50	
<b>Laminate</b>				
Thickness	ISO 534	µm	127±3	

#### Application and use

For use in logistics labelling, commercial and general labelling.

#### Converting and Printing

Suitable for digital, flexo and offset printing as well as TTR, thermal transfer printing.

#### Packaging

The rolls are sliced according to customer requirements, packed with shrink films and paperboards are placed on sides. They are delivered on pallets. Product description labels are fixed on rolls.

#### Shelf Life and Storage Conditions

Two years when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 22 °C ± 2 °C with a relative humidity of 50 %, ± 5%.

All information and recommendations about FRİMPEKS products are based on our existing knowledge and experiences but do not mean a guarantee or warranty. As the products are used for different applications we recommend to check suitability of product prior to use. All information is subject to change without notice.

FRİMPEKS KİMYA VE ETİKET SAN TİC. A.Ş.

Mermerciler Sanayi Sitesi 8. Cad. No:15 34520, Beylikdüzü, İstanbul / TÜRKİYE

T : + 90 (212) 876 07 10

F : + 90 (212) 876 07 17

e-mail : info@frimpeks.com.tr

www.frimpeks.com.tr

